

MC55i-W



Quad-Band



Highly
Compact Size



GPRS
Class 10



RIL Driver




TCP/IP
Connectivity



FAX Functionality



Tunneling Mode



2G

Cinterion® MC55i-W Wireless Module
Quad-Band Miniaturized

Cinterion® MC55i-W Wireless Module

Quad-Band Miniaturized


Following up the successful MC55i wireless module, the new MC55i-W offers improved functionality while remaining compatible with its predecessor and enable an extended life cycle for customers application.

Alongside highest reliability and quality the module is based on the latest generation of 2G products offering Quad-Band, full voice capabilities and high speed GPRS class 10 data transmission and is your all-rounder of choice for board-to-board designs in machine-to-machine communication including metering, security, vending, POS and many more applications.

MC55i-W offers improved features such as a significantly reduced power consumption, an extended temperature range and the new tunneling mode. This mode allows to simplify the direct link of Near Field Communication (NFC) devices, sensors or GPS receivers to the micro controller of the host application, helping to lower the total cost of ownership for implementers.

Like all Cinterion modules it comes with full type approval (FTA) enabling use across the globe. It has even been certified by the largest carriers worldwide, including US operators.

Quad-Band Miniaturized



Tunneling mode

A smart way that allows the microcontroller to control any device that has a serial interface like GPS receiver or NFC device through the module and enable transparent communication.

Software stack based on 3GPP Release 99

Update of GSM standard. Release '99 introduces higher speed data transmission using Enhanced Data Rates for GSM Evolution (EDGE) to improve network stability.

Gemalto M2M Support includes:

- > Personal design-in consulting for hardware and software
- > Extensive RF test capabilities
- > GCF/PTCRB conform pretests to validate approval readiness
- > Regular training workshops



Local engineers, a competent helpdesk, a dedicated team of R&D specialists and an advanced development center are the hallmarks of our leading support offer.

Cinterion® MC55i-W Features

GENERAL FEATURES

- > Quad-Band GSM
850/900/1800/1900 MHz
- > 3GPP Release 99
- > GPRS multi-slot class 10
- > Compliant to GSM phase 2/2+
- > Output power:
 - > Class 4 (2 W) for EGSM850
 - > Class 4 (2 W) for EGSM900
 - > Class 1 (1 W) for GSM1800
 - > Class 1 (1 W) for GSM1900
- > Control via AT commands
(Hayes 3GPP TS 27.007, TS 27.005)
- > SIM Application Toolkit
- > TCP/IP stack access via AT commands
- > Internet Services: TCP Server/Client, UDP, HTTP, FTP, SMTP, POP3
- > Supply voltage range: 3.3 ... 4.8 V
- > Power consumption typically:
 - > Power down: 45 μ A
 - > Sleep mode
(fully registered DRX = 9): 1.3 mA
 - > Speech mode (850/900MHz): 180 mA
 - > GPRS class 10 (850/900MHz): 230 mA
- > Operating Temperature Range:
 - > -40 °C to +85 °C
 - > Protective shutdown
 - > Storage: -40 °C to +85 °C
- > Dimensions: 35 x 32.5 x 2.95 mm
(incl. B-to-B-Connector: 3.1 mm)
Weight: 5.5 g

SPECIFICATIONS

- > GPRS class 10: max. 86 kbps (DL)
- > Mobile station class B
- > PBCCH support
- > Coding schemes CS 1-4
- > Triple-rate codec for HR, FR, and EFR
- > Adaptive multi-rate AMR
- > Basic hands-free operation
- > Echo cancellation
- > Noise reduction
- > CSD Data Transmission Up to 14.4 kbps, V.110, Non-transparent mode
- > USSD support
- > Fax Group 3, class 2 and class 1
- > SMS text and PDU mode, cell broadcast

SPECIAL FEATURES

- > Customer IMEI as variant

INTERFACES

- > 50-pin board-to-board connector
 - > Power supply
 - > Audio: 1 x analog, 1 x digital
 - > SIM card interface 1.8 V, 3 V
 - > 2 x serial interface (ITU-T V.24 protocol)
- > U.FL-R-SMT 50 Ω antenna connector
- > Antenna solder pad

DRIVERS

- > RIL driver for Microsoft® Windows Mobile™ based devices
- > Multiplex driver for Microsoft® Windows XP™, Windows 7 and Microsoft® Windows Vista™

APPROVALS

- > Local approvals and network operator certifications
- > R&TTE, FCC, UL, IC, GCF, PTCRB, CE

For more information, please visit

m2m.gemalto.com, www.facebook.com/gemalto, or Follow @gemaltom2m on twitter.

The information provided in this brochure contains merely general descriptions or characteristics of performance, which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. All product designations may be trademarks or product names of Gemalto M2M GmbH or supplier companies whose use by third parties for their own purposes could violate the rights of the owners. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners. ARM9 is a registered trademark of ARM Limited.

Gemalto M2M GmbH
St.-Martin-Str. 60
81541 Munich
Germany



➔ M2M.GEMALTO.COM

gemalto
security to be free