


cable detail RG58 (Leoni Dacar 110)



1. Inner conductor

Material: Cu tinned
Diameter: 0.90 mm

2. Dielectric

Material: PE
Diameter: 2.95 mm

3. Outer conductor

Material: Copper
Diameter: 4.95 mm

4. Jacket

Material: PVC

Characteristics

Impedance: 50 Ω
Capacity at 1kHz: 105 pF / m
Conductor resistance @ 20°C: 41 Ω/km
Velocity of propagation: 66 %
Attenuation @ 1GHz: 60.4 dB/100m
Attenuation @ 2GHz: 92.7 dB/100m
Attenuation @ 3 GHz: 126.3 dB/100m
Operating temperature: -40°C .. +85°C
Cable weight: 39.0 kg/ km

Verfügbare Längenvariante
L = 0,3m RG58-KABEL-SMA-N-002
L = 0,7m RG58-KABEL-SMA-N-003
L = 1m RG58-KABEL-SMA-N-001
L = 10m RG58-KABEL-SMA-N-010

weitere Längen und Konfigurationen auf Anfrage



Toleranzen nach ISO 2768-1-(SG)

Erstellt

Herr K.Heinze

Freigabe

Frau S. Grote

Sachnummer

RG58-KAB-SMA-N-0xx

Titel

SMA-St / N-St
RG58 - Kabel

Dokumentenart

DIN A 4

Maßstab

1:1

Änd.

Ausgabedatum

17.06.2022

Spr.

DE

Blatt

1/1